


## FEEDER SPECIFICATION/送材機機型資料

|  |  |                                     |             |
|--|--|-------------------------------------|-------------|
| <b>CO-MATIC Model / 型號</b>                         |  |                                     | <b>AF19</b> |
| <b>Overall Dimension/整體尺寸</b>                      | <b>British / 英制</b>  | <b>Metric / 公制</b>                  |             |
| Height (w/ Handle) / 高(含把手)                        | 12-1/4"  | 310 mm                              |             |
| Width / 寬  | 13"  | 330 mm                              |             |
| Length (w/ Handle and Arm Fully Extended) / 長(含把手) | 43"  | 1090 mm                             |             |
| Net Weight / 淨重                                    | 176 Lb   | 79 Kg                               |             |
| Gross Weight / 毛重                                  | 209 Lb   | 97 Kg                               |             |
| Packing Size / 包裝尺寸                                | 48"×18-7/8"×18-1/2"  | 1220×480×470 mm                     |             |
| <b>Construction/結構</b>                             |  |                                     |             |
| Columns / 管  | Cast Iron  | 鑄鐵                                  |             |
| Column Diameter / 管徑                               | φ2-1/4"  | φ58                                 |             |
| Fence / 導板   | Cast Iron  | 鑄鐵                                  |             |
| Housing / 機身                                       | Cast Iron  | 鑄鐵                                  |             |
| Sprockets / 心軸                                     | JIS #S45C  | 中碳鋼 JIS #S45C                       |             |
| Rollers / 送料輪                                      | φ6-7/8"×1-9/16"×2PCs/ Cast Steel (optional with PU roller)                         | φ175x40mm×2只/ 鑄鋼                    |             |
| <b>Motor/馬達</b>                                    |  |                                     |             |
| Type / 類型  | TEFC Capacitor Start Induction   | 臥式直心式                               |             |
| Horsepower / 馬力                                    | 1/2 HP (1 or 3 Phase)  | 0.375 KW (單 或 三相)                   |             |
| Rotation / 正反轉                                     | Forward  | 正轉                                  |             |
| Bearings / 軸承                                      | Deep Groove Ball Bearing #6***   | 深溝滾珠軸承 #6***                        |             |
| <b>Specifications/詳細規格</b>                         |  |                                     |             |
| Number of Speeds / 送料速度                            | 10 Speeds  | 10 速                                |             |
| Range of Speeds / 速度範圍 (50Hz)                      | 3.5/7/7.1/11/14/20/22/25/40/50 FPM   | 1/2/2.3.5/4/6/7/7.5/12/15 M/min     |             |
| Range of Speeds / 速度範圍 (60Hz)                      | 4/8.5/8.5/14/17/25/28/30/50/60 FPM   | 1.5/2.5/2.5/4/5/7.5/8/9/15/18 M/min |             |
| Max. Height of Rollers(OD) / 送料輪最大高度               | 5-1/2"   | 140 mm                              |             |
| Swing / 旋轉   | 30°  | 30°                                 |             |
| Max. Roller-Blade Clearance / 送料輪擺臂最大距離            | 8-1/4"   | 200 mm                              |             |
| Fence Size / 導板規格                                  | 15-3/4"L x 7-7/8"  | 400L x 200 mm                       |             |
| Max. Fence-Blade Clearance / 導板伸縮最大距離              | 8-1/4"   | 210 mm                              |             |

PS : Specifications subject to changes without prior notice. / 任何規格改變概不另行通知